

PRODUCT DESCRIPTION

Asian paints Decora Sanding Sealer Concentrated is based on Nitrocellulose. It is suitable for furniture and other timber surfaces that require good sealing and excellent sanding properties. It forms a smooth surface coating for application of topcoat. It has excellent durability and good adhesion.

AREAS OF APPLICATION

Wooden Furniture, Paneling

PRODUCT INFORMATION

Pack size	200ml, 500ml, 1 liter, 4 liter and 200 liter drums on request
Shade / Colour range	Available in Clear, Teak, Mahogany and Black
Method of Application	By brush or spray

TECHNICAL INFORMATION/ DATA

Thinner	Autocare NC GP Thinner
Thinning ratio (by vol.)	One part of sealer to two parts of Autocare NC GP Thinner for spray Application. 1 – ½ parts Thinner for Brush application
Spreading Rate	12 – 15 m ² per liter per coat depending on the surface porosity and texture.
Drying time at 30 ⁰ C	
Cotton free	5 minutes
Hard dry / Recoatability	1 –2 hours
Sanding time	1 –2 hours

SURFACE PREPARATION

Select well-seasoned wood for coating. If previously coated, remove the coating by sanding. Sand the surface using emery paper 180 followed by emery paper 320 or 400. Clean the surface to free of dust & contaminants prior to application of sealer

APPLICATIONS DETAILS

Apply by brush or spray and allow drying for 2 hours. Flatten with fine abrasive paper. Continue this process until a smooth even surface is obtained. Top coat with Asian paints NC Lacquer or PU varnish.

Flammability and Transport Information

Highly flammable

SAFETY INFORMATION AND PRECAUTIONS

- Avoid open flame, heat and sparks
- Use only with adequate ventilation
- Avoid prolonged breathing of vapour or contact with skin.
- Store in a cool dry place
- If contact with skin clean with recognized cleanser
- If contact with eyes, flush with clean water for about 15 minutes & seek medical advise
- Avoid any heat or flame
- Keep out of reach of children

CONTACT US

For further information, or if you have any queries about using this product, please contact our office at:

Asian Paints (Lanka) Ltd.
81, Korlawella Road, Moratuwa.

Ph: 011-2658621-4
Fax: 011-2658200

Website: www.asianpaints.com
Email id: contact@asianpaints.lk

DISCLAIMER

Although the facts and suggestion in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.